

## EXIDE Sonnenschein

Dryfit A500  
Design Life 6 - 9 Jahre

Für Sicherheit und Notstrom



Artikel Nr.	Type	Nennspannung V	Nennkapazität K20 1,75 V/Z 20°C Ah	Innenwiderstand mOhm	Kurzschlussstrom A	Maße mm max.			Höhe über Anschl. H2 mm	Gewicht ** ca. kg	Anschluss
						L	B	H			
20.05129	A502/10S	2	10	11,2	189	52,9	50,5	94,5	98,4	0,7	S-4,8
20.05132	A504/3,5S	4	3,5	48,0	88,0	90,5	34,5	60,5	64,4	0,5	S-4,8
20.05134	A506/1,2S	6	1,2	165	38,0	97,3	25,5	51	55,6	0,33	S-4,8
20.05147	A506/3,5S	6	3,5	71	88,0	135	34,8	60,5	64,4	0,70	S-4,8
20.05151	A506/6,5S	6	6,5	48	131	152	34,5	94,5	98,4	1,3	S-4,8
20.05152	A506/10S*	6	10	34	189	152	50,5	94,5	98,4	2,1	S-4,8
20.05148	A508/3,5S	8	3,5	95	88,0	179	34,1	60,5	64,4	1,0	S-4,8
20.05149	A512/1,2S*	12	1,2	330	38,0	97,5	49,5	51	54,9	0,65	S-4,8
20.05153	A512/2S*	12	2,0	172	73,0	179	34,1	60,5	64,4	1,0	S-4,8
20.05154	A512/3,5S*	12	3,5	142	88,0	135	66,8	60,5	64,4	1,5	S-4,8
20.05155	A512/6,5S*	12	6,5	95,0	131	152	65,5	94,5	98,4	2,6	S-4,8
20.05156	A512/10,0S*	12	10,0	66,0	189	152	98,0	94,5	98,4	4,0	S-4,8
20.05157	A512/16G5*	12	16,0	37,8	340	181	76,0	167	167	6,0	G-M5
20.05158	A512/25G5*	12	25,0	28,0	463	167	176	126	126	9,6	G-M5
20.05160	A512/40A*	12	40,0	16,5	770	210	175	175	175	14,2	A
20.05161	A512/40G6*	12	40,0	16,5	770	210	175	175	175	14,2	G-M6
20.05162	A512/55A	12	55,0	10,9	1147	261	135	208	230	18,1	A
20.05165	A512/60A	12	60,0	14,0	936	278	175	190	190	20,3	A
20.05166	A512/65A	12	65,0	8,30	1471	353	175	190	190	23,0	A
20.05167	A512/65G6	12	65,0	8,30	1471	353	175	190	190	23,0	G-M6
20.05163	A512/85A*	12	85,0	7,40	1693	330	171	213	236	29,2	A
20.05164	A512/115A	12	115,0	5,50	2275	286	269	208	230	37,5	A

\* VDS Zulassung

\*\* Tatsächliches Gewicht kann um ±5% abweichen.

Max. Belastung nur bei entsprechender Gegenkontaktierung.

Anschlussarten:

