

YUASA

Valve-Regulated (Sealed) Lead-Acid
Wartungsfreie, wiederaufladbare Blei-AGM Akkumulatoren
6V – 12 V

Design Life 3 – 5 Jahre



Artikel-Nr.	Typen-Nr.	Nenn- Spannung V	Nennkapazität K20 Ah	Maße mm			Gewicht kg	VE
				L	B	H*		
20.06404	NP1.2-6	6	1,2	97	25	54,5	0,31	40
20.06407	NP3-6	6	3	134	34	64	0,70	40
20.06408	NP4-6	6	4	70	47	105,5	0,87	20
20.06411	NP7-6	6	7	151	34	97,5	1,32	16
20.06413	NP12-6 VdS	6	12	151	50	97,5	2,05	10
20.06316	NP0.8-12	12	0,8	96	25	61,5	0,35	20
20.06415	NP1.2-12 VdS	12	1,2	97	48	54,5	0,58	20
20.06317	NP2-12	12	2	150	20	89	0,70	20
20.06419	NP2.3-12 VdS	12	2,3	178	34	64	0,96	20
20.06422	NP3.2-12	12	3,2	134	67	65	1,20	10
20.06423	NP4-12	12	4	90	70	106	1,75	10
20.06425	NP7-12 VdS	12	7	151	65	97,5	2,20	8
20.06426	NP7-12I VdS	12	7	151	65	97,5	2,20	8
20.06428	NP12-12 VdS	12	12	151	98	97,5	4,05	4
20.06429	NP17-12I VdS	12	17	181	76	167	6,10	4
20.06431	NP24-12I VdS	12	24	166	175	125	9,00	2
20.06433	NP38-12I VdS	12	38	197	165	170	14,20	2
20.06435	NP65-12I VdS	12	65	350	166	174	23,00	1

* Höhe über Pol